OGUE 2013 SPRINTCHIMICA


SPRINTCHIMICA CATALOGUE 2013



importation from countries of origin P.zza A.Vivaldi, 3,4,5 50069 Loc. Sieci (Firenze) Italy

Ph. +39 055 8309116 - 8328221 r.a. Fax +39 055 8363722

www.sprintchimica.it sprint@sprintchimica.it





MANUFACTURE OF SOLVENTS, THINNERS AND CHEMICAL PRODUCTS FOR TRADE AND PRODUCTION



SPRINTCHIMICA spa

We enjoy talking about our birth immediately after the war.

We feel like brave pioneers. We started off as **Sprint** and quickly established ourselves thanks to the burning desire to grow and rebuild that characterised many people at that time. We supplied small regional companies, which were also founded in that era, with thinners and other products. Our products were mainly of plant origin such as essence of turpentine and pine oil, imported from Asia, a continent that has inspired us and to which our logo is still linked even today.

With the growth of the market and research in the chemical industry, our product range has expanded and evolved, addressing mainly oil-based products. With the increase in demand the distribution area expanded continuously, affirming our position as the forerunner of an activity we were totally committed to and making us undisputed market leaders.

During the 1970s we moved, expanded, increased raw material storage and changed our name to **Sprintcolor**.

It is in our current premises that our final transformation to **SPRINTCHIMICA SpA** took place in 1985, still ahead of the times with the supplying of bulk solvents to dye factories, leather tanning industries, manufacturers of ink, mastic, adhesive tape and many others. Study, continuous research and curiosity opened up our knowledge and subsequently to the marketing of products related to the petrochemical industry but with different destinations and usages: products for professional construction, protective coatings for wood and iron and a wide range of chemical products in general, for the DIY and automotive sectors and destined both for professional applications (body shops, repair-shops) and traders in the sector. Today we operate extensively throughout the country with a network of our own representatives, paying particular attention to the quality and proper management of all products formulated by us or simply marketed by us, following guidelines of Responsible Care and Responsible Distribution programs and laws of quality certification ISO 9000.

All our products are packaged, transported and marketed in compliance with applicable laws, particularly with regard to the labelling of individual products in terms of safety, updated to reflect the latest EU directives, so to allow for proper handling by the end user. All packages have a special secure closure for child safety and braille indications of danger for the blind.

Each product is also available in barrels and in bulk as well as in containers customized by the client.



thinners Sprint Line pg. 02 - 08 white spirit and synthetic thinners Sprint Line pg. 09 - 12 paint removers Sprint Line pg. 13 raw materials Sprint Line pg. 14 - 18 oils • Sprint Line pg. 19 - 24 **lubricants** pg. 25 bitumen and tar pg. 26 glue pg. 27 anti-woodworm pg. 28 automobile cleansing pg. 29 fillers and mastic Sprint Line pg. 30 - 33 powders, cement and plaster pg. 34 - 35 technical products pg. 36 - 37 chemical products pg. 38 - 41

dyes, pigments

wax and paraffin

special products

new generation paint products

in spray can

Product list

productsGallo Line

chemical products

paint products and solvents

water-based paint products





pg. 42 - 43

pg. 44 - 45

pg. 46 - 47

pg. 50 - 57

pg. 58 - 61

pg. 62 - 65

pg. 48

pg. 49







NC ANTI-FOG THINNER NC EXTRA

A nitro anti-fog thinner of very high quality, consistently formulated with the purest raw materials, without the addition of chlorinated substances. It has excellent anti-bleaching power and is particularly suitable in sectors where high quality nitro anti-fog thinners are needed.

To dilute paints: add the required amount of Nitro Thinner NC to the product until you get the desired viscosity, following the instructions on the packaging of the product to be diluted, in accordance with the Directive on limitation of emissions of Volatile Organic Compounds (VOCs) n.2004/42/EC. In accordance with the same directive, it may be used at the car body shops to wash

For cleaning brushes: wash thoroughly until all paint has been removed. The use of protective clothing and gloves is recommended.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F

R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 S2 • S16 • S33 •S36/37 • S46











NC ANTI-FOG THINNER S/65

It is a nitro anti-fog thinner particularly suitable for nitrocellulose coatings, both for iron and wood. Has good anti-bleaching power and can be used in above average humidity conditions. It makes paints shiny, allowing for good dilution while maintaining chemical characteristics.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F

R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 S2 • S16 • S29 • S33 •S36/37 • S46

NC ANTI-FOG THINNER 2013

This product was specifically designed for thinning nitro and nitrosynthetic paints and enamels, to be applied by brush or spray. It has a mild and tolerable odour. It has a high solvent power and balanced evaporation to allow for good flow and rapid drying of the coating product.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	







P301+P310 • P331 • P405 • P501





EURODIL THINNER

A UNIVERSAL thinner suitable for diluting mono-component paints, both quick-drying and synthetic types. It has excellent solvent and anti-fog power, with a very low odour. It makes nitrosynthetic and acrylic paints brighter, once dry. We wanted to be especially careful about making a product in the thinners segment which, due to its characteristics, complies with all the new EU rules on components used to provide the end user with a product classified exclusively as an Xi IRRITANT.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	



R11 • R36 • R66 • R67 S2 • S9 • S16 • S25 • S33 • S46





PU POLYURETHANE THINNER

Thinner formulated with the purest raw materials which are balanced in order to obtain a product suitable for the dilution of one-component and two-component polyurethane paints. It is particularly used in painting furniture and precious objects.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F

R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 S2 • S16 • S33 • S36/37 • S46

PU SLOW POLYURETHANE THINNER

Thinner formulated with the purest raw materials which are balanced in order to obtain a product suitable for the dilution of one-component and two-component polyurethane paints. It is particularly used in painting furniture and precious objects.

Package	Capacity	Pieces	Price
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F

R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 S2 • S16 • S33 •S36/37 • S46 DILUENTE PER SPARTITRAFFICO

rubber resins.




DILUENTE PER CLOROCAUCCIÓ



THINNER FOR CHLORINATED RUBBER

Thinner for dilution or dissolution of chlorinated rubber resins.



THINNER FOR MARKING PAINT

A thinner characterised by a mixture of

solvents with a high evaporation rate and is

therefore suitable as a thinner for marking

paints, made with mixtures of chlorinated



R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 S2 • S16 • S29 • S33 •S36/37 • S46

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F

R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 S2 • S16 • S29 • S33 •S36/37 • S46





THINNER FOR MASTICS

Universal thinner for normal, PVC, neoprene mastics and others. Great for cleaning brushes, spatulas and other utensils utilised for mastic.



ANTI-SILICONE THINNER

It is a thinner specifically used to eliminate traces of silicone, wax, grease from iron structures or vehicle bodies, before painting.



AC THINNER FOR ACRYLIC

Specific thinner for acrylic paints which does not alter the brightness and the mechanical strength of the enamel.



EPOXY THINNER

Formulation of pure raw materials designed and tested for optimal dilution of varnishes and epoxides, results in maximum applicability and expansion, improving the final result.

AC SLOW THINNER FOR ACRYLIC

Package	Capacity	Pieces	Price
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F-N R11 • R36/38 • R51/53 • R65 • R66 • R67 S2 • S16 • S29 • S33 • S46 • S61

Package	Capacity	Pieces	Price
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F-N R11 • R51/53 • R65 • R66 • R67 \$2 • \$16 • \$29 • \$33 • \$46 • \$61

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F R11 • R36/38 • R48/20 • R63 • R65 • R66 • R67 S2 • S13 • S16 • S33 • S36/37 • S46

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	













RETARDANT FOR NC AND PU THINNER

The use of this retardant is recommended when, due to very specific atmospheric conditions such as excessive heat, high humidity, fog, a non-homogeneous and more opalescent coating is obtained. About 2-3% of this corrective substance must be added, although the percentages may vary depending on atmospheric conditions.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	



H332 • H312 • H302 • H319 • H315 P101 • P102 • P280 • P301+P312 • P501





SYNTHETIC THINNER VM

Specific thinner for synthetic and alkyd enamels , flattings, anti-corrosion products, primer products, air-dry coatings and enamels. Its strong solvent power allows for better application of the paint with a brush or spray enhancing brilliance and ease of application. Excellent for cleaning brushes and tools.



Xn-N

R10 • R51/53 • R65 • R66 • R67 S2 • S16 • S29 •S33 •S36/37 • S46 • S61



thinners

white spirit and synthetic thinners

















ODOURLESS EXTRA SYNTHETIC THINNER

Its use as a solvent for synthetic and alkyd paint and enamel is recommended, specifically for application in closed and delicate environments, thanks to low odour and reduced harmful effects due to the absence of aromatics.

TRE GEMME THINNER

A mineral white spirit with the addition of denaturing products in accordance with current tax laws. Ideal for thinning synthetic, alkyd and oil enamels and paints, synthetic primers, anti-corrosion products; improves application with brush or spray. Excellent for cleaning brushes and tools.

ACQUARAGIA WHITE SPIRIT 150

Specific product for the dilution of synthetic and alkyd enamels and paints, oil paints, anticorrosion products and matt coatings; improves application by brush or spray, enhancing brilliance. Excellent for cleaning brushes.

GEMMA SPRINT PURE THINNER

The essence of turpentine from pure pine bud, with superior quality and very pleasant smell; ideal for thinning fine art paint, solid wax for furniture and wooden and Tuscan tile floors, matt coatings, synthetic and alkyd enamel and grease.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	-







EUH066 P101 • P102 • P210 • P280 • P301+P310 • P501

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	



F-Xn-N R11 • R20/21/22 • R36/38 • R48/20 • R51/53 • R63 • R65 • R66 • R68/20/21/22 \$2 • \$16 • \$29 •\$33 •\$36/37• \$46 • \$61

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	







H225 • H304 • H336 • H411 EUH066 P101 • P102 • P210 • P271 • P280 • P301+P310 • P501

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	175 Kg	1	







H226 • H332 • H312 • H302 • H304 • H319 • P301+P312 • P501



white spirit and synthetic thinners













SYNTHETIC THINNER FOR BAKED **COATINGS**

Specific product specially formulated with pure raw materials for the dilution of synthetic enamels used in baked coatings.

RAGIOLINA

Dearomatised white spirit It is recommended for use as a solvent for synthetic varnishes and paints for painting places such as hospitals, schools, restaurants, public buildings and all places where a strong odour should be avoided. Thanks to the absence of aromatic products, it exudes very little odour and has very low toxicity. It is also used in washing and degreasing floors, fabrics and surfaces in general.

STRIPPER PAINT REMOVER

Stripper Paint Remover: Good value paint remover. Ideal for removing wall paint from indoor and outdoor surfaces, solvent or water based enamels, from wood and metal surfaces. It is a transparent gel that can be applied vertically. Non caustic.

FREE FROM DICHLOROMETHANE

DECOSPRINT STRONG PAINT REMOVER

Strong and effective paint remover for quick removal of synthetic alkyd enamels, baked or air-dry coatings, wall hydropaint and nitrocellulose, polyester and polyurethane paints. It is applied with a brush and does not drip. It is not caustic and therefore does not damage wood and metal. Thanks to its new formulation, it is now more stable and has more paint removing power.

FREE FROM DICHLOROMETHA

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-N R10 • R37 • R51/53 • R65 • R66 • R67 S2 • S16 • S29 • S33 • S46 • S61

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

R10 • R65 • R66 • R67 S2 • S13 • S16 • S33 • S43A • S46

Package	Capacity	Pieces	Price
Can	0,75 Litre	12	1/2 1/4
Barrel	3 Litre	4	-43
Barrel	15 Litre	1	
		N	<u> </u>







~	~	
		• H319 • H <mark>37</mark>
P101 • P	102 • P210 •	P271 • P280
P301+P3	312 • P405 •	P501

Package	Capacity	Pieces	Price
Can	0,75 Litre	12	
Barrel	3 Litre	4	
Barrel	17 Litre	1	
Barrel	200 Litre	1	
Sfuso	1000 Litre	1	





P101 • P102 • P210 • P280 • P305+P351+P338 • P337+P313 • P501



white spirit and synthetic thinners







PURE ACETONE

Solvent for numerous natural and synthetic resins, it is almost universally used in a myriad of application fields such as the cosmetics industry as a solvent for nail polish, in the industrial sector for the production of adhesives, dyes, paints and for selective extraction in the pharmaceutical, footwear and carpentry sectors. It is widely used for anything that requires high solvent power and rapid evaporation.

Package	Capacity	Pieces	Price
Phial	0,25 Litre	12	
Can	0,5 Litre	20	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	



H225 • H319 • H336 P101 • P102 • P210 • P280 •P312 • P501



WHITE KEROSENE OIL

Refined product. Suitable for cleaning and degreasing in the fields of mechanical and typographic lithography and serigraphy.



SOLVENT FOR SHELLAC

99° alcohol mixture for domestic and industrial uses. Particularly suitable for dissolving shellac flakes and thinning shellac-based paint such as our SPRINT SHELLAC SOLUTION. Excellent for cleaning toilets and floors, when used in 5-10% water solution.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel*	5 Litre	4	
Barrel*	20 Litre	1	
Barrel*	200 Litre	1	



H304 • EUH066 P101 • P102 • P262 • P301+P310 • P331 •

^	^	
Barrel		200 Litr
Barrel		20 Litre
Barrel		5 Litre

Package

Phial

Phial



Capacity

0,5 Litre

1 Litre

H225 • H319 • H336 P101 • P102 • P210 • P271 • P280 •P312 •

*while supplies last







90° DENATURED ETHYL ALCOHOL

Denatured ethyl alcohol 90° is the most used for normal domestic purposes, employing its solvency power to clean and disinfect.



94° DENATURED ETHYL ALCOHOL

Denatured ethyl alcohol 94° is used in the handicraft and industrial sectors for the production of shellac-based paints for wood. It can be used for normal domestic purposes, employing its high solvency power to clean and disinfect.



99,9° DENATURED ETHYL ALCOHOL

Denatured ethyl alcohol with DGS at 99,9° is most used in the handicraft and industrial sectors for the production of shellac-based paints for wood, for the production of printing ink and for the preparation of pharmaceutical products. Used to solve shellac flakes.



STAIN REMOVER T.R.

It is a product with a pleasant smell, created specifically for removing stains from fabric and leather. For its high solvent power when it comes to grease, oil and wax, it can be used for cycles of cold degreasing and anti-silicone sheet treatment. Very suitable for cleaning clock and alarm clock gears.

Package	Capacity	Pieces	Price
Phial	0,5 Litre	24	
Phial	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

F R11 S2 • S6 • S16 • S46

Package	Capacity	Pieces	Price
Phial	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

F R11 S2 • S6 • S16 • S46

Package	Capacity	Pieces	Price
Phial	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

F R11 S2 • S6 • S16 • S46

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-F-N R11 • R38 • R51/53 • R65 • R67 \$2 • \$16 • \$29 •\$33 • \$46 • \$61







TRIELCLOR

Ideal for removing stains from fabrics, carpets, leather.

Excellent as a cold degreaser. (You should try the product on a small area to verify compatibility with the fabric)

Package	Capacity	Pieces	Price
Phial	0,25 Litre	12	
Phial	0,375 Litre	12	
Can	0,5 Litre	20	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	300 Kg	1	









H226 • H351 • H304 • H315 • H317 • H336 • H411 P101 • P102 • P210 • P271 • P280 • P301+P312 • P331 • P405 • P501





BOILED LINSEED OIL (TRIPLE BOI-LED)

Produced with high drying power, it has many uses because of its features: suitable for protecting and waterproofing wood fixtures and beams and can be painted with synthetic paints and enamel following treatment. It is also used for the preparation of anti-corrosion products, synthetic finishes, filler and mastic as well as printing ink and lithographs.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	









Package

Can

Barrel

Barrel

Capacity

1 Litre

5 Litre

20 Litre

200 Litre

Pieces

12

4

Price

Clear and shiny vegetable oil, sediment-free; it is raw linseed oil supplemented by specific products that make it ideal in the preparation of the foundation for Florentine tile flooring.



















PARAFFIN OIL B/50

Duty-paid vaseline oil, colourless, odourless, tasteless. It is used as a lubricant for both domestic and industrial uses, even in the food processing industry. It is used in the cosmetic and pharmaceutical industries due to its extreme purity.

SPRINTOIL OIL CATCHER WITH SPOUT

Package	Capacity	Pieces	Price
Oil catcher	0,2 Litre	24	
Phial	0,25 Litre	12	
Phial	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

PLASTOIL T.A. (WOOD OIL) STRAW YELLOW

Denatured alkylated product, suitable for domestic and industrial applications, used as polish for wooden furniture.

It is applied with a buffer, pure or diluted with Tre gemme white spirit. After applying polish with a soft cloth.

Restores cleanliness and shine to wood. Water repellant

RED PLASTOIL (WOOD OIL)

Denatured alkylated product, suitable for domestic and industrial applications, used to polish and brighten the colour of wooden furniture.

It is applied with a buffer, pure or diluted with Tre gemme white spirit. After applying polish with a soft cloth.

Restores cleanliness, brilliance and hue to the wood colour.

Water repellant.

Package	Capacity	Pieces	Price
Phial	0,25 Litre	12	
Phial	0,5 Litre	12	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	



H304 • EUH066 P101 • P102 • P301+P310 • P331 • P405 • P501

Package	Capacity	Pieces	Price
Phial	0,25 Litre	12	
Phial	0,5 Litre	12	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	



H304 • EUH066 P101 • P102 • P301+P310 • P331 • P405 • P501





WHALE OIL

Glossy synthetic finish. Apply with a buffer for the polishing of varnish on antique furniture, gives a smooth surface. Dilute with 3Gemme thinner or vm synthetic thinner. Can also be used on raw wood as a neutral protective agent.



EMULSIFIABLE OIL (RELEASE AGENT FOR CEMENT)

Emulsifiable oil with emulator additives which ensure extremely stable milky emulsions in water. It is suitable for cutting and processing steel, iron, cast iron with lathes and drills. It is also used as a release agent on reinforced concrete.



LEMON GRASS VEGETABLE OIL

Thanks to its special formulation, it creates an invisible barrier against mosquitoes allowing you to rest assured outdoors during warm summer evenings. Specially for garden and terrace torches.



GALLOIL

Produced with quick drying product, it has many uses because of its features: suitable for protecting and waterproofing wood fixtures and beams and can be painted with synthetic paints and enamel following treatment. It is also used for the preparation of anti-corrosion products, synthetic finishes, filler and mastic as well as printing ink and lithographs.



Xn-N R10 • R51/53 • R65 • R66 • R67 S2 • S16 • S29 • S33 • S46 • S61

Package	Capacity	Pieces	Price
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Package	Capacity	Pieces	Price
Phial	1 Litre	12	

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

R52/53 S2 • S46







PINE OIL

Essential oil obtained from the distillation of pine buds and needles, has a pleasant odour and is widely used in industry for the preparation of perfumes, soaps, deodourants and cosmetics for its organoleptic characteristics. It is a good solvent for rosin, kauri and other resins. Excellent as a perfume for hydro paint for interiors.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	20 Litre	1	



H319 • H315 P264 • P280 • P302+P352 •P332+P313



STAUFFER BIO-GREASE

Grease with good water resistance, suitable for the lubrication of machines typically operating at moderate temperatures and loads. It is particularly suitable for ball bearings, roller bearings, wheels, gears, compressors, pumps and various utensils.

WHITE PETROLEUM JELLY

Has a protective anti-rust and anti-corrosion action on iron; as an antioxidant it is ideal for electrical cables, batteries, painted, anodized, chrome surfaces.



Package	Capacity	Pieces	Price
Jar	0,25 Litre	12	
Jar	0,5 Litre	12	
Jar	1 Litre	12	
Jar	5 Litre	1	
Jar	175 Kg	1	









Protective penetrating sealer for wood. Used for wooden structures that need to be underground It is advisable to treat the wood at least 20 cm above the ground level. Monocomponent product to use as is without diluting.

Rapid drying at temperatures above 20°C.

The use of protective clothing and gloves

The use of protective clothing and gloves is recommended.

FOR PROFESSIONAL USE

Package	Capacity	Pieces	Price
Can	0,75 Litre	12	
Barrel	5 Litre	4	







H225 • H361d • H304 • H373 • H315 • H336 P201 • P210 • P280 • P301+P310 • P304+P340 • P370+P378 • P501

EDILBLACK

Bituminous black paint dissolved in a solvent with a high tar content. It is used on cement, wood and iron as a protective coating. Due to its viscosity it is applied by brush or roller, without dilution, being a ready to use product. It can be used as antiqued patina of wooden structures such as antique furniture and ceiling beams; for this type of penetrating sealer, it is very important to dilute the product with our NC EXTRA NITRO THINNER.

The use of protective clothing and gloves is recommended.

FOR PROFESSIONAL USE

Package	Capacity	Pieces	Price
Can	0,75 Litre	12	
Barrel	5 Litre	4	







H225 • H361d • H304 • H373 • H315 • H336 P201 • P210 • P280 • P301+P310 • P304+P340 • P370+P378



POWDER JELLY GLUE

Non-food jelly glue ideal for laminating all glue of animal origin.

Package	Capacity	Pieces	Price
Jar	750 GR	6	
Barrel	25 Kg	1	



CLEAR BEAD GLUE

Glue of animal origin, finds its main use in the rubber band industry, in binding books and magazines, in envelope packaging and bonding of luggage and carpentry.

Package	Capacity	Pieces	Price
Jar	750 GR	8	
Barrel	25 Kg	1	



LAPIN GLUE

Also known as rabbit-skin glue. It is used in restoration and in the gilding sector. It is a very elastic glue that is prepared by adding about 0.500 I. of water to 1 Kg of glue, heating it all in a bainmarie up to 60°/70°.











SPRINTCHIMICA ANTI-WOODWORM

Protective residual insecticide, odourless, colourless. It is a product designed and formulated to eliminate termite and other wood pests. Medical surgical device N° 19064 authorised by the Ministry of Health.



Package	Capacity	Pieces	Price
Phial	0,25 Litre	24	
Jar	1 Litre	12	
Barrel	2,5 Litre	6	

Xn-N R50/53 • R65 • R66 S2 • S13 • S29 • S46 • S61



"NUOVA LINDA" HAND WASH CREAM

Lanolin hand wash cream, designed and formulated for cleaning hands. Excellent for garages, body shops and industries in general. Does not crack the skin and does not clog the sink drain.

Package	Capacity	Pieces	Price
Jar	1 Litre	24	
Jar	4 Litre	6	



detergent for automobiles





painting.

Jar

Jar

Jar

Barrel

Container



French paste filler, excellent spreadability and

can be sanded. Mono-component filler with

very little shrinkage, suitable for wood and

interior walls. It does not create halos after

24

12

4

FLY STUCK WHITE PASTE

250 Gr

500 Gr

1 Kg

5 Kg

25 Kg





THOSE METALLIES

for car bodies. Easy application and can be sanded. Essential in obtaining a smooth and homogeneous surface before painting. Gray







POLYESTHER PUTTY FOR WOOD

Filler for wood including catalyst. Excellent as a filler for wood, easy to sand and can be worked with tools such as planers, drills, saws. It can be coloured with Sprintchimica iron oxides and painted with any type of paint or enamel.





Available colours:

WALNUT • MAHOGANY• PINE • DOU-GLAS • OAK

Package	Capacity	Pieces	Price
Jar	500 Gr	12	

Package	Capacity	Pieces	Price
Jar	0,125 Litre	18	
Jar	0,750 Litre	6	

Xn R10 • R20 • R36/37/38 • R48 S2 • S3 • S16 • S23 •S33 • S46

Package	Capacity	Pieces	Price
Jar	0,125 Litre	18	
Jar	0,750 Litre	6	

Xn R10 • R20 • R36/37/38 • R48 S2 • S3 • S16 • S23 • S33 • S46







POLYESTHER PUTTY FOR DARK WOOD

Filler for wood including catalyst. Excellent as a filler for wood, easy to sand and can be worked with tools such as planers, drills, saws. It can be coloured with Sprintchimica iron oxides and painted with any type of paint or enamel.

Package	Capacity	Pieces	Price
Jar	0,125 Litre	18	
Jar	0,750 Litre	6	

Xn R10 • R20 • R36/37/38 • R48 S2 • S3 • S16 • S23 • S33 • S46



POLYESTHER PUTTY FOR MARBLE

Mastic for vertical marble including catalyst. Excellent as a filler and as glue for marble and granite.

Package	Capacity	Pieces	Price
Jar	0,125 Litre	18	

Xn R10 • R20 • R36/37/38 • R48 S2 • S3 • S16 • S23 • S33 • S46



FIBREGLASS REPAIR KIT

Resin and glass wool, separated, including catalyst. Suitable for the maritime industry or to repair fibreglass structures. Kit composition: 0.750 I polyester resin with catalyst, 0.5 sqm glass wool fabric, 1 glass, 1 brush, 1 disposable glove.

Package	Capacity	Pieces	Price
Kit	0,750 Litre	6	

Xn R10 • R20 • R36/37/38 • R48 S2 • S3 • S16 • S23 •S33 • S46

LIQUID POLYESTER RESIN

Liquid polyester resin for sealing including catalyst. Easy to apply and very adherent to the surface.

Package	Capacity	Pieces	Price
Container	0,750 Litre	6	
Jar	5 Litre	4	

Xn R10 • R20 • R36/37/38 • R48 S2 • S3 • S16 • S23 •S33 • S46



FIBREGLASS RINFORCED POLYESTHER RESIN

Resin and incorporated glass wool including catalyst. Ideal product for to repair fibreglass structures, spoilers and places which need plaster with strong grip. Green.

Package	Capacity	Pieces	Price
Jar	0,125 Litre	18	
Jar	0,750 Litre	6	

Xn R10 • R20 • R36/37/38 • R48 S2 • S3 • S16 • S23 • S33 • S46

FIBERGLASS MAT

Package	Capacity	Pieces	Price
Bags	0,5 Mq	10	





















READY PLASTER

Package	Capacity	Pieces	Price
Box	1 Kg	12	
Sack	5 Kg	5	

Xi R36/37/38 • R41 • R43 S2 • S22 • S24/25 • S26 •S36/37 • S46

GLUE FOR TILES

Package	Capacity	Pieces	Price
Box	1 Kg	12	
Sack	5 Kg	5	

Xi R36/37/38 • R41 S2 • S22 • S24/25 • S26 •S36/37 • S45

WHITE • GREY CEMENT

Package	Capacity	Pieces	Price
Box	1 Kg	12	
Sack	5 Kg	5	

Xi R36/37/38 • R43 S2 • S22 • S24/25 • S26 •S36/37 • S46





POWDER PLASTER

Package	Capacity	Pieces	Price
Вох	1 Kg	12	
Sack	5 Kg	5	

SCAGLIOLA (MAREZZO MARBLE) PLASTER

Package	Capacity	Pieces	Price
Box	1 Kg	12	
Sack	5 Kg	5	

QUICK • REFRACTORY CEMENT

Package	Capacity	Pieces	Price
Box	1 Kg	12	
Sack	5 Kg	5	

Xi R36/37/38 • R41 • R43 S2 • S22 • S24/25 • S26 •S36/37 • S46

FLY STUCK POWDER

Smoothing filler diluted with water as needed and is very workable and spreadable, does not shrink. Suitable for interior surfaces.

Package	Capacity	Pieces	Price
Вох	1 Kg	12	
Sack	5 Kg	5	
Sack	25 Kg	1	





AMERICAN NATIONAL STEEL WOOL

- FURNITURE MANUFACTURERS
- ROLLS

Steel wool for cleaning structures, for smoothing wood, removing paint. The grains are differentiated into: national (coarse) - American (fine) - furniture manufacturers (very fine) - rolls (average).





MASKING TAPE

Paper adhesive tape specific to the professional construction industry, decorations, murals, etc..

Surface: semicrepe paper Adhesive: natural rubber



CLEAR ADHESIVE TAPE

Package	Length	Rolls	Price
Cartons	48x66 y	36	

Length	Rolls	Price
19x50 y	96	
25x50 y	72	
30x50 y	60	
38x50 y	48	
50x50 y	36	
	19x50 y 25x50 y 30x50 y 38x50 y	19x50 y 96 25x50 y 72 30x50 y 60 38x50 y 48

AVANA ADHESIVE TAPE

Package	Length	Rolls	Price
Cartons	48x66 y	36	









HYDROCHLORIC ACID (PURE)

Hydrochloric acid or also known as muriatic acid at a high concentration of 33.

Used for washing, degreasing, descaling and surfaces and pipes and other objects, provided they are not metal. It is a corrosive product, always use adequate protection for the hands and eyes during use.

Package	Capacity	Pieces	Price
Phial	1 Litre	12	
Canister	5 Litre	4	
Canister	20 Litre	1	



 \Diamond

H290 • H314 • H335 P101 • P102 • P280 • P310 • P390 • P403+P233 • P501



CAUSTIC SODA

Pure product for domestic and industrial applications to be diluted 30% to 70% in water depending on needs. It is a corrosive product to be used very carefully even if it is packaged in a convenient jar with safety cap. Dose for lye: 30/40 gr caustic soda per litre of water.



SODA ASH - SOLVAY

It is widely used in the glass, detergent, paper, ceramic and textile industries. For domestic use to wash and degrease surfaces and to reduce water hardness. It is an ideal degreasing agent diluted with hot water for interiors of demijohns and flasks.



Package	Capacity	Pieces	Price
Jar	1 Litre	12	
Sack	25 Kg	1	



H290 • H314 P101 • P102 • P280 • P310 • P405 • P501

Package	Capacity	Pieces	Price
Thermo	0,750 Kg	12	



H319 P101 • P102 • P264 • P280 • P305+P351+P338 • P337+P313v • P501



chemical products



PARALOID

This is an acrylic bead resin, soluble in acetone or nc extra anti-fog thinner or denatured ethyl alcohol. It is used to consolidate objects and structures made of wood, marble, stone. It is applied with a brush for better impregnation on immersion Non-yellowing.



DRAIN DEBLOCKER HYDRAULIC FLUID

It is a liquid specifically designed to clare pipes clogged by organic deposits and aggregates; penetrates stagnant water and acts quickly. Strong Use the product with extreme care and caution.



Creolina ® Disinfectant Medical and Surgical Reg. Ministry of Health 148/10

Excellent descaling from the characteristic odour. Diluted in water to treat toilets, kennels, poultry and rabbit farms.



SHELLAC FLAKES (CLEAR)

It is a natural resin from India, soluble in alcohol or solvent for shellac for the preparation of alcohol-based paints. It is used for polishing antique furniture with a pad.



Package	Capacity	Pieces	Price
Phial	0,750 Litre	12	



H314 P101 • P102 • P280 • P320 • P405 • P501

Package	Capacity	Pieces	Price
Can	1 Litre	12	
Barrel	5 Litre	4	

N-Xn

R21/22 • R38 • R41 • R43 • R51/53 S2 • S13 • S26 • S36/37/39 • S46 • S29/56 • S61

Package	Capacity	Pieces	Price
Sack	5 Kg	1	
Bale	25 Kg	1	
Case	50 Kg	1	







MORDANT POWDER

Mordant powder available in Walnut and Mahogany. They are used mainly dissolved in water and acetone for colouring coarse wood; the desired shade for the colouring of the body structure or a touch-up, depends on the dilution.

OSSIDO GIALLO

Package	Capacity	Pieces	Price
Jar	0,5 kg	6	
Sack	25 Kg	1	

EARTH DYES

Colours: English rose P11, black, burnt umber, golden yellow. Earth dyes, soluble in water and in oil Used for colouring mineral products and as loader for mono-component acrylic filler. In the decoration sector they are needed to formulate decorative patina.

Package	Capacity	Pieces	Price
Jar	0,75 kg	6	
Sack	25 Kg	1	

IRON OXIDES

Colours: blue, green, red, flower yellow, black, brown. Synthetic iron oxides, soluble in water and in oil. Used for colour in various sectors, from construction to paint factories.

Package	Capacity	Pieces	Price
Jar	0,5 kg	6	
Sack	25 Kg	1	



TINGO WOOD

The professional universal colouring "TingoLegno" can be used both for colouring sealing agents and water-based and solvent coatings for wood and for direct wood colouring. The coverage per layer is from 12 sqm. to 15 sqm. per litre depending on the absorption of the wood.

Package	Capacity	Pieces	Price
Phial	0,2 Litre	8	

R10 S2 • S24/25 • S43a • S46

See colour chart

WAX STICKS

Coloured wax sticks of pure wax are used to repair and fill small scratches and dents in wood, to close holes caused by termites as well as for filling small cracks in the wood. The wax sticks are used by pressing the stick itself directly on the part to be repaired or filled. The wax sticks are available in 12 colours.

See colour chart



CREO COLORS

The professional universal colourants "CreoColors" have no painting function, are compatible with most paint products such as hydro paint, quartz, synthetic enamels, nitro enamels, water-based enamels etc. .. and do not alter the technical characteristics of the products themselves. For special products such as polyester and elastic paint, it would be better to conduct compatibility tests. These dyes are highly concentrated for strong colouring power. Therefore, an application of 5/6% of the paste to the product to be coloured is sufficient for an intense shade: Can be blended. They are resistant to frost during storage.

Package	Capacity	Pieces	Price
Phial	45 ml	12	
Phial	0,5 Litre	4	

See colour chart







NITRO PRIMER WOOD FILLER

Transparent wood filler, nitrocellulosebased, fast-drying. Suitable for closing the pores of wood and for preparing surfaces for subsequent finishing operations.

Once dry, sand the surface with fine sandpaper (220-240 grain) and dust well before applying further coats of finish. It is applied with a brush, paying attention to the drying time elapsing between the application of the two coats. It also applied by diluted spray like our NC EXTRA NITRO ANTI-FOG THINNER until the desired viscosity is obtained, in compliance with the Directive on the limitation of emissions of Volatile Organic Compounds (VOCs) n.2004/42/EC.

The use of protective clothing and gloves is recommended.

FOR PROFESSIONAL USE

Package	Capacity	Pieces	Price
Jar	0,75 Litre	6	
Barrel	4 Litre	2	







H225 • H361d • H304 • H373 • H319 • H315 • H336 P201 • P210 • P280 • P301+P310 • P304+P340 • P370+P378

















GRAFIX N.S.

Synthetic semi-gloss enamel is applied in the wrought iron sector as a primer and finish for iron; it does not crack nor wear with time. Smooth: Grafix NS

Package	Capacity	Pieces	Price
Jar	0,125 Litre	18	
Jar	0,375 Litre	24	
Jar	0,750 Litre	18	
Jar	4 Litre	2	



R10 • R52/53 • R65 • R66 • R67

NITRO PAINT

In the 30 gloss shiny and matt version. Excellent finish for wood and iron, to be applied by diluted spray with nc extra nitro anti-fog thinner.

Package	Capacity	Pieces	Price
Jar	0,75 Litre	12	
Barrel	4 Litre	2	







H225 • H361 • H304 • H373 • H319 • H315 • P201 • P210 • P280 • P301+P310 • P304+P340 • P370+P378

SHELLAC SOLUTION

Original Indian shellac dissolved in alcohol mixture at 99°, with added anti-bleaching chemical products. We use it pure and undiluted, as a primer for precious wood. For use as a protective and polishing agent of wood, dilute the shellac solution up to 100% with SOLVENT FOR SHELLAC SPRINT or our ethanol d.g.s. to 99°.

Package	Capacity	Pieces	Price
Phial	0,25 Litre	12	
Phial	0,5 Litre	12	
Phial	1 Litre	12	



H225 • H319 P101 • P102 • P210 • P280 • P305+P351+P338 • P337+P313 • P501

COLOUR FACTORY

The colours represented here are purely indicative

Gallo Line ACRYLIC PAINT SPRAY 100%

Colours: See RAL colour chart

Acrylic paint spray of excellent quality and brilliance. Each spray can has a cap coloured according to the colour content.

Also available: Gold - silver - aluminium wheels - anti-rust.

Package	Capacity	Pieces	Price
Spray can	0,4 Litre	6	



R12 • R36 • R66 • R67 S2 • S23 • S26 •S33 • S45 • S51





and solvent

products





LIQUID ACRYLIC SHEATH Colours: white - grey - red oxide

Elastomeric hydro paint with ease of brushing and very good grip. It is suitable for waterproofing concrete surfaces and can be applied on bituminous coatings. Good coverage depending on the surface where it is applied.

Package	Capacity	Pieces	Price
Jar	0,75 Litre	6	
Jar	2,5 Litre	1	
Jar	5 Litre	1	
Jar	14 Litre	1	



HYDROPAINT FOR INTERIORS (RED CAP)

White hydro paint for interiors. Good performance, diluted by up to 100% of its volume. By its nature, it is not reach in resin and therefore is not powdery; therefore permits a breathable surface.

Package	Capacity	Pieces	Price
Jar	2,5 Litre	1	
Jar	5 Litre	1	
Jar	14 Litre	1	

BREATHABLE FOR INTERIORS (BLUE CAP)

Hydro paint for interiors diluted up to 100% high-coverage, great brightness.

Package	Capacity	Pieces	Price
Jar	14 Litre	1	

BREATHABLE HYDROPAINT FOR INDOORS/OUTDOORS (WHITE CAP)

White hydro paint for interiors and for outdoors. Good performance, diluted by up to 100% of its volume. By its nature, it is reach in resin and this allows a good adherence to the surface. Washable.

Package	Capacity	Pieces	Price	
Jar	2,5 Litre	1		
Jar	5 Litre	1		
Jar	14 Litre	1		

water-based





PARAFFIN SLABS

A mixture of saturated aliphatic hydrocarbons is used in various industrial sectors: those of the manufacture of candles and tealights, textile and many others.

Package	Capacity	Pieces	Price
Slab	5 kg	1	
Slab	25 kg	1	

BEESWAX

Pure natural wax, used in the cosmetics industry and for the preparation of skin creams and waxes for hair removal. It is also used in the manufacture of floor and furniture wax.

Package	Capacity	Pieces	Price
Slab	5 kg	1	







MAGIK CONVERTER RUST CONVERTER

Blocks rust permanently and transforms it into a protective layer of dark colour perfectly anchored to the surface and therefore ideal for painting.



Xi R10 • R36 • R67 S2 • S25 • S26 • S43 • S46







WASSER LACK SPECIFIC THINNER FOR WATER-BASED PRIMERS

Technological product formulated with raw materials selected specifically for the dilution of water-based paint products.

Water-based thinner for dilution of primers for wood such as penetrating agents, glazes and paints with acrylic primer; and for iron as anti-rust

Dilute up to 10%; Non flammable; facilitates the application of the product significantly improving the verticalisation and ease of brushing as well as the drying process. The product evaporates slowly so the tools can be left soaking in a container for a few days. Has no volatile organic content (VOC FREE) so does not alter the characteristics of the product when VOC is added

Package	Capacity	Pieces	Price
Phial	1 Litre	12	

WASSER LACK SPECIFIC THINNER FOR WATERBASED ENAMELS

Technological product formulated with selected raw materials specific for the dilution of pigmented water-based enamels, both for indoors and outdoors. Water-based thinner for dilution of satin and glossy enamel. Dilute up to 10%, Non flammable; facilitates the application of enamel considerably improving verticalisation and ease of brushing as well as the drying process. The product evaporates slowly so the tools can be left soaking in a container for a few days. Has no volatile organic content (VOC FREE) so does not alter the characteristics of the product when VOC is added.

Package	Capacity	Pieces	Price
Phial	1 Litre	12	

WASSER LACK SPECIFIC THINNER FOR WATER-BASED PAINTS

Technological product formulated with selected raw materials specific for the dilution of transparent water-based varnishes, both for indoors and outdoors. Water-based thinner for dilution of wood coatings such as glossy and satin flatting, wax-effect finishes, penetrating agents. Dilute up to 10%, Non flammable; facilitates the application of paint considerably improving verticalisation and ease of brushing as well as the drying process. The product evaporates slowly so the tools can be left soaking in a container for a few days. Has no volatile organic content (VOC FREE) so does not alter the characteristics of the product when VOC is added.

Package	Capacity	Pieces	Price
Phial	1 Litre	12	

new denerati

new generation paint products





Acrylic-based wall insulation. (100% acrylic resin) Suitable for indoor and outdoor use. It has strong consolidating power; well suited to avoiding differences in absorption of the plaster and ensuring perfect placement of paint.

COVERAGE: 8/10 SQM LITRE, PRODUCT DILUTED WITH WATER 1 TO 10. (depending on the absorbency of the surface)

Package	Capacity	Pieces	Price
Jar	0,375 Litre	6	
Jar	0,750 Litre	6	
Jar	2,5 Litre	2	





HOLZ LACK ACRYLIC UNDERCOAT FOR WOOD AND WALLS

White, brown, grey-green water-based undercoat (sub-enamel). Specifically for wood and walls, easily sanded, is indispensable for the preparation of water-based synthetic paints. Product for indoors and outdoors.

5/6 SQM. COVERAGE LITRE REFERS TO 2 UNDERCOATS OF PRODUCT (depending on the absorbency of the surface)



STOPPER FLECK ANTI-SMOKE ANTI-STAIN WALL INSULATION, COLOUR WHITE

Wall paint solvent. Primer-finish, for difficult wall surfaces.

Odourless, non-yellowing, non-drip. Blocks the reappearance of nicotine stains, smoke, soot and grease.

Insulates surfaces and does not permit the reappearance of covered spots. It is washable with water and mild detergent. Ready to use product for indoors.

5/6 SQM. COVERAGE LITRE REFERS TO 2 UNDERCOATS OF PRODUCT (depending on the absorbency of the surface)

Package	Capacity	Pieces	Price
Jar	0,375 Litre	6	
Jar	0,750 Litre	6	
Jar	2,5 Litre	2	

R53 • R66 S2 • S23 • S29 • S46 • S51 • S61



METALL LACK ANTI-RUST WATER-BASED ACRYLIC FOR METAL

Anti-corrosive water-based primer for iron, light alloys and galvanized iron.

Free of lead chromates. Excellent coverage, anti-corrosive, strong adhesion Paint for primer layer, in water dispersion, physically drying mono-component, matt, acrylic binder, odourless. Colours: Grey, Orange.

5/6 SQM. COVERAGE REFERS TO 1: UNDERCOAT OF PRODUCT (depending on the absorbency of the surface)


Package	Capacity	Pieces	Price
Jar	0,375 Litre	6	
Jar	0,750 Litre	6	
Jar	2,5 Litre	2	

R52/53 S2 • S46 • S61



new generation paint products





yellowing with good saturation. One-component. Product suitable for wood structures in sea and mountain areas.

7/8 SQM. COVERAGE REFERS TO 1

UNDERCOAT OF PRODUCT (depending on the absorbency of the surface)



WATER-BASED PROTECTIVE WAX **EFFECT PAINT**

Valuable water-based water-repellent finish. Wax effect mono-component. Definitive treatment for weather protection. Satin, natural, acrylic, for indoors and outdoors. Odourless paint with velvety appearance and anti-UV filter, non-yellowing Product suitable for wood structures in sea and mountain areas.

9/12 SQM. COVERAGE REFERS TO UNDERCOAT OF PRODUCT (depending on the absorbency of the surface)



HOLZ SCHULZ WATER-BASED PENETRATING AGENT FOR WOOD

Water-based opaque protection for wood, deep penetrating, odourless, mono-component, does not create a film.

Colours: Transparent, light walnut, dark walnut, mahogany, chestnut, douglas.

9/12 SQM. COVERAGE REFERS TO 1 UN-DERCOAT OF PRODUCT (depending on the absorbency of the surface)

Package	Capacity	Pieces	Price
Jar	0,375 Litre	6	
Jar	0,750 Litre	6	
Jar	2,5 Litre	2	

Package	Capacity	Pieces	Price
Jar	0,375 Litre	6	
Jar	0,750 Litre	6	

2,5 Litre

Package	Capacity	Pieces	Price
Jar	0,375 Litre	6	
Jar	0,750 Litre	6	

Product formulated with special raw materials

which make it suitable for blocking rust on iron

structures, both on the surface and in depth.

Insulates the structure from the elements,

18/20 SQM. COVERAGE REFERS TO 1

UNDERCOAT OF PRODUCT (depending on

STOPPEN RUST

creating a thin film.

the absorbency of the surface)

RUST BLOCK

ckage	Capacity	Pieces	Price
r	0,375 Litre	6	
r	0,750 Litre	6	
r	2,5 Litre	2	

generai

new generation paint products



PARKETT GLANZ **WATER-BASED GLAZE FOR PARQUET**

Mono-component water-based transparent glossy paint (75 gloss minimum) Ready to use, odourless. Primer finish Protective antiscratch for shiny wood Washable with mild detergents.

7/8 SQM. COVERAGE REFERS TO 1 UNDERCOAT OF PRODUCT (depending on the absorbency of the surface)







SCHIMMEL WASCHEN WALL MOULD SANITISER

Sanitiser for walls affected by mould. Recommended for particularly deteriorated surfaces and a broad spectrum of action.



SCHIMMEL STOPPEN ANTI-MOULD ADDITIVE FOR HYDRO **PAINT**

Single-dose of anti-mould to be included in 5 litres of water-based hydro paint for indoor and outdoor use. Prevents the formation of mould. Particularly suitable for walls subject to condensation and moisture.

Package	Capacity	Pieces	Price
Jar	0,375 Litre	6	
Jar	0,750 Litre	6	
Jar	2,5 Litre	2	

Package	Capacity	Pieces	Price
Phial	0,200 Litre	6	
Phial	1 Litre	6	

S2 • S16 • S28 • S36/37 • S46

Package	Capacity	Pieces	Price
Phial	0,200 Litre	6	

Xi-N R43 • R51/53 S2 • S24 • S28 • S29 • S36/37 • S46 • S61

new generation paint products





MAGIK TOGLISILICONE SILICONE REMOVAL SPRAY

Preparation essential for effortless removal of silicone residue hardened by: fixtures, steel, glass, plastic laminates, marble and ceramics.



MAGIK SBLOCK UNBLOCKING SPRAY

Ideal for loosening threaded joints, fittings, screw clamps, nuts, bolts, blocked by oxidation and rust.



Package	Capacity	Pieces	Price
Spray can	0,4 Litre	12	

Package	Capacity	Pieces	Price
Spray can	0,4 Litre	12	

F+ R12 S2 • S9 • S23 • S43 • S46 • S51 F+ R12 • R66 S2 • S9 • S23 • S46 • S51



F+-Xi-N R12 • R38 • R51/53 S2 • S18 • S23 • S29 • S46 • S51 •S61

chemical products in spray can



MAGIK ZINCO COLD GALVANISER SPRAY

Rust inhibitor containing zinc alloy, silver grey colour. Ideal for classic galvanising
Once the product is applied, the structure can

Once the product is applied, the structure can be painted with any type of paint, after drying for at least 48 hours.



MAGIK CATENE GREASE SPRAY

Ideal for protecting and lubricating all moving and still mechanical parts.

The special composition of the preparation allows it to penetrate where other products normally do not penetrate.

Its high viscosity makes it particularly effective for fast moving mechanical parts without being ejected by the centrifugal force. Does not crack and protects all metals from atmospheric corrosion.



MAGIK SILICONE SILICONE SPRAY

Ideal for protecting and waterproofing. It is used as a release agent for rubber moulds and plastic, it is recommended for the maintenance of ski bindings, reels for fishing rods, winches, boats, gear tents and porches. Eliminates squeaks from car doors and all rubbing parts protecting them from moisture.



MAGIK CONVERTITORE RUST SPRAY CONVERTER

Blocks rust permanently and transforms it into a hard protective layer of dark colour, perfectly anchored to the substrate and therefore ideal for painting.



Package	Capacity	Pieces	Price
Spray can	0,4 Litre	12	

Package	Capacity	Pieces	Price
Spray can	0,4 Litre	12	

Package	Capacity	Pieces	Price
Spray can	0,4 Litre	12	

Package	Capacity	Pieces	Price
Spray can	0,4 Litre	12	

Xi-F+-N R12 • R36 • R50/53 • R66 • R67 S2 • S18 • S23 • S29 • S46 • S51 • S61 F+ R12 • R52/53 S2 • S9 • S18 • S23 • S43 •S46 • S51 Xi-F+-N R12 • R38 • R51/53 • R67 S2 • S9 • S16 • S23 • S29 • S46 • S51 • S61 Xi-F+ R12 • R36 • R67 S2 • S18 • S23 • S25 • S46 •S51





SYNTHETIC THINNER

Specific thinner for synthetic enamels and syntheticoleo, flattings, anti-rust products, primer products, air-dry coatings and enamels. Its strong solvent power allows for better application of the paint with a brush or spray enhancing brilliance and ease of application. Excellent for cleaning brushes and tools.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn-N R10 • R20/21/22 • R51/53 • R65 • R66 S2 • S16 • S29 •S33 •S36/37 • S46 • S61

NC ANTI-FOG THINNER

It is a nitro anti-fog thinner particularly suitable for nitrocellulose coatings, both for iron and wood. Has good anti-bleaching power and can be used in conditions of humidity above

It makes the paint glossy, allowing for good dilution and maintaining their chemical characteristics.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 \$2 • \$16 • \$29 • \$33 •\$36/37 • \$46

SUPER NC ANTI-FOG THINNER

It is a nitro anti-fog thinner of very high quality, consistently formulated with the purest raw materials, without the addition of chlorinated substances. It has excellent antibleaching power and is particularly suitable in sectors where high quality nitro anti-fog thinners are needed.

PU POLYURETHANE THINNER

Thinner formulated with the purest raw materials which are balanced in order to obtain a product suitable for the dilution of one-component and two-component polyurethane paints. It is particularly used in painting furniture and precious objects.

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

R11 • R20/21/22 • R36/38 • R48/20 • R63 • R65 • R66 • R68/20/21/22 S2 • S16 • S33 •S36/37 • S46

Package	Capacity	Pieces	Price
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

R11 • R20/21/22 • R36/38 • R48/20 • R63 •

R65 • R66 • R68/20/21/22 S2 • S16 • S33 •S36/37 • S46





DEAROMATISED ODOURLESS WHITE SPIRIT

Dearomatised white spirit It is recommended for use as a solvent for synthetic varnishes and paints for painting places such as hospitals, schools, restaurants, public buildings and all places where a strong odour should be avoided. Thanks to the absence of aromatic products, it exudes very little odour and has very low toxicity. It is also used in washing and degreasing floors, fabrics and surfaces in general.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

Xn R10 • R65 • R66 • R67 S2 • S13 • S16 • S33 • S43A • S46

REGINA WHITE SPIRIT

A mineral white spirit with the addition of denaturing products in accordance with current tax laws. Ideal for thinning synthetic, alkyd and oil enamels and paints, synthetic primers, anti-corrosion products; improves application with brush or spray. Excellent for cleaning brushes and tools.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

n-N R10 • R20/21/22 • R51/53 • R65 • R66 S2 • S16 • S29 •S33 •S36/37• S46 • S61

GALLOIL

Produced with high drying power, it has many uses because of its features: suitable for protecting and waterproofing wood fixtures and beams and can be painted with synthetic paints and enamel following treatment. It is also used for the preparation of anti-corrosion products, synthetic finishes, filler and mastic as well as printing ink and lithographs.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	20	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

R52/53

BOILED LINSEED OIL (TRIPLE BOILED)

Produced with high drying power, it has many uses because of its features: suitable for protecting and waterproofing wood fixtures and beams and can be painted with synthetic paints and enamel following treatment. It is also used for the preparation of anti-corrosion products, synthetic finishes, filler and mastic as well as printing ink and lithographs.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	

RAW LINSEED OIL

Clear and shiny vegetable oil, sediment-free; it is raw linseed oil supplemented by specific products that make it ideal in the preparation of the foundation for Florentine tile flooring.

Package	Capacity	Pieces	Price
Can	0,5 Litre	20	
Can	1 Litre	12	
Barrel	5 Litre	4	
Barrel	20 Litre	1	
Barrel	200 Litre	1	





ACETALS

DIOXOLANE METHYLAL

ACETATES

BUTYL ACETATE

BUTYLDIGLYCOL ACETATE

BUTYLGLYCOL ACETATE

ETHYL ACETATE

ISOBUTYL ACETATE

METHYL ACETATE 80%-90%-98%

PMA - METHOXYPROPYLACETATE

ALCOHOLS

ETHANOL DENATURED D.G.S. 90°- 94°- 99,9° *

ISOBUTANOL

ISOPROPANOL*

N-BUTANOL

ALIPHATICS

CICLOHEXANE*

DSP 100/140 *

HEPTANE*

HEXANE*

ISOHEXANE*

N-DECANE *

OCTANE *

AROMATICS

STYRENE

TOLUENE*

XYLENE (MIXTURE OF ISOMERS) *

CHLORINATED

DICHLOROMETANE

DICHLOROPROPANE

TETRACHLOROETHYLENE

ESTERS

DBE - DIBUTYL ESTER

DIDP - ISODECYL PHTALATE

DINP - ISONONYL PHTALATE

DOA - DIOCTYL ADIPATE

GLYCOL ETHERS

BUTYLDIGLYCOL

BUTYLGLYCOL

DPM - DIPROPYLENE GLYCOLMETHYL ETHER

ETHYLDIGLYCOL

PM - METHOXYPROPANOL

GLYCOLS

DIETHYLENE GLYCOL

ETHYLENE GLYCOL

MONOETHYLENE GLYCOL

MONOPROPYLENE GLYCOL

HYDROCARBONS

ISOPARAFFINE J*

WHITE SPIRIT *

WHITE SPIRIT DEAROMATIZED

D/30 - D/40 - D/60 - D/80 - D/100 *

WHITE PETROLEUM *

NAPHTA SOLVENT 100 *

KETONES

ACETONE

CYCLOHEXANONE

4-HYDROXY-4-METYLPENTAN-2-ONE

MEK - METHYL ETHYL KETONE

MIBK - METHYL ISOBUTYL KETONE

OILS

ALKYL DERIVATES - STRAW OIL

LINESEED OIL

WHITE MINERAL OIL (PETROLEUM) *

TERPENS

D-LIMONENE

PINE OIL

TURPENTINE





^{*} Products under control of Customs Office.

"R" RISK STATEMENTS

R10 Inflammable R11 Very inflammable R12 Extremely Inflammable R20 Harmful by inhalation R22 Harmful by ingestion R20 Harmful in contact with skin R22 Harmful by ingestion R34 R35 Causes burns Causes severe burns R36 R37 Irritating to the eyes Irritating to respiratory system R38 Irritating to skin R39 Very serious irreversible danger R40 Limited evidence of a carcinogenic effect R41 R42 Risk of serious damage to eyes May cause sensitisation by inhalation

R43 May cause sensitisation by skin contact R48 Danger of serious damage to health by prolonged exposure

R50 Very toxic to aquatic organisms R51 Toxic to aquatic organisms R52 Harmful to aquatic organisms

R53 R60 May cause long-term adverse effects in the aquatic environment

May impair fertility

R61 May cause harm to the unborn child R62 R63 Possible risk of impaired fertility Possible risk of harm to unborn children R65 Harmful: may cause lung damage if swallowed R66 R67 Repeated exposure may cause skin dryness or cracking

Vapours may cause drowsiness and dizziness

R68 Possible risk of irreversible effects R20/21 Harmful by inhalation in contact with skin R21/22 Harmful in contact with skin and if swallowed R20/22 Harmful by inhalation and if swallowed R20/21/22 Harmful by inhalation, ingestion and skin contact R36/37 Irritating to eyes and respiratory system R37/38 Irritating to respiratory system and skin

R36/38 Irritating to eyes and skin

R36/37/38 Irritating to eyes, respiratory system and skin

R48/20 Harmful: danger of serious damage to health in case of prolonged exposure through inhalation R48/21 Harmful: danger of serious damage to health by prolonged exposure in contact with skin R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed

R48/20/21 Harmful: danger of serious damage to health by prolonged exposure through inhalation and skin contact R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed R48/21/22 Harmful: danger of serious damage to health by prolonged exposure in contact with skin and if swallowed R48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, skin contact

and if swallowed

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment R51/52 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R68/20 Harmful: possible risk of irreversible effects through inhalation R68/21 Harmful: possible risk of irreversible effects in contact with skin R68/22 Harmful: possible risk of irreversible effects if swallowed

R68/20/21 Harmful: possible risk of irreversible effects through inhalation and in contact with skin R68/20/22 Harmful: possible risk of irreversible effects through inhalation and if swallowed R68/21/22 Harmful: possible risk of irreversible effects in contact with skin and if swallowed

R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed

PRECAUTIONARY "S"

S1	Keep locked
S2	Keep out of reach of children
S9	Keep container in a well ventilated place
S13	Keep away from food and beverages, including those for animals
S16	Keep away from sources of ignition. No smoking.
S18	Handle and open container with care
S23	Do not breathe gas vapours, fumes, spray (appropriate wording specified by the manufacturer)
S24	Avoid contact with skin
S25	Avoid contact with eyes
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S28	After contact with skin, wash immediately with plenty of (appropriate product specified by the manufacturer)
S29	Do not empty into drains
S33	Take precautionary measures against static discharges
S36	Wear suitable protective clothing
S37	Wear suitable gloves
S38	In case of insufficient ventilation, make use of an appropriate breathing device
S43	In case of fire use (extinguishers specified by the manufacturer.
	If risk increases in the presence of water, add: "Never use water")
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas
S53	Avoid exposure, obtain special instructions before use
S57	Use appropriate container to avoid environmental contamination
S60	This material and/or its container must be disposed of as hazardous waste
S61	Avoid release to the environment. Refer to special instructions/safety data sheets
S62	If swallowed, do not induce vomiting: seek medical advice immediately
S1/2	Keep locked tightly closed
S24/25	Avoid contact with the eyes and with the skin
S36/37	Wear suitable protective clothing and gloves
	•







EASILY FLAMMABLE

"F+" EXTREMELY INFLAMMABLE

Wear suitable protective clothing, gloves and protect eyes/face



DANGER TO THE IRRITANT



"Xi"

"Xn" **HARMFUL**

The information related to labelling of dangerous products may vary.

Always check the indications on danger and related symbols against the corresponding safety data sheets.



risk statements and safety advice

REGULATION (EC) No 1272/2008 - HAZARD "H"

Physical dangers

H225 Easily flammable liquids and vapours.
H226 Flammable liquids and vapours.
H290 May be corrosive to metals.

Dangers to the health

H302 Harmful if ingested.

H304 May be fatal if swallowed and enters airways.
H312 Harmful if it comes into contact with skin.
H314 Causes severe skin burns and eye damage

H315 Causes skin irritation.

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H332 Harmful if inhaled.

H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H315 Suspected of causing cancer

H361 Suspected of causing cancer

H373 May cause damage to organs through prolonged or repeated exposure

Dangers to the environment

H411 Toxic to aquatic life with long lasting effects
H412 Harmful to aquatic life with long lasting effects

Properties hazardous to health

EUH066 Repeated exposure may cause skin dryness or cracking

REGULATION (EC) No 1272/2008 - PRECAUTIONARY "P"

General safety advice

P271

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe dust / fumes / gas / mist / vapours / spray.

P262 Avoid contact with eyes, skin or on clothing.

P264 Wash thoroughly after use.

Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

Precautionary statements - Reaction

P310 Immediately call a POISON CENTRE or doctor.

P312 If you feel unwell, contact a POISON CENTRE or doctor.

P313 Consult a doctor.

P320 Specific treatment is urgent (see on this label).

P331 Do NOT induce vomiting.

P332 If skin irritation occurs:

P301+P310 If swallowed, immediately contact a POISON CENTRE or doctor.

P301 + P312 In case of ingestion, call a poison control centre or physician if you feel unwell.

P302+P352 In case of contact with skin: Wash with plenty of soap and water.

P304+P340 In case of inhalation: Remove victim to fresh air and keep at rest in a position that permits

comfortable breathing.

P305+P351+P338 In case of contact with eyes: Rinse carefully with water for several minutes. Remove any contact lenses

if easy to do. Continue rinsing.

P337+P313 If eye irritation persists, consult a doctor.

P370+P378 In case of fire: Use foam, dry powder or carbon dioxide (CO2).

P390 Absorb spillage to prevent material damage.

Precautionary statements - Conservation

P405 Store locked up.

P403+P233 Keep container tightly closed and in a well ventilated area.

Precautionary statements - Disposal

P501 Dispose of contents / container according local laws.











The information related to labelling of dangerous products may vary.

Always check the indications on danger and related symbols against the corresponding safety data sheets.

no catons

indications of danger and precautionary statements

NOTE:

